

Part Number: TO56-114

High Power TO56 Package Multi-Mode Fabry-Perot Pulsed Wavelength at 1310nm Lensed Options Available

Features

- High Output Power
- High Dynamic Range
- High Efficiency
- Standard TO56
- Cost Effective

Application

Home Use Medical





SemiNex delivers the highest available power at infrared wavelengths between 12xx and 19xx nm. When necessary, we will further optimize the design of our InP & GaSb laser chips to meet our customers' specific optical and electrical performance needs. Diodes, bars and packages are tested to meet customer and market performance demands. Typical results and packaging options are shown. Contact SemiNex for additional details or to discuss your specific requirements.

SemiNex Corporation • 153 Andover Street, Suite 201, Danvers, MA 01923 • 978-326-7700 • sales@seminex.com



Specification

TO56-114



Optical	Symbol	Тур.	Units
Center Wavelength	λ _c	1310	nm (±20)
Output Power (<10ns)*	Pout	42	Watts (±10%)
Output Power (150ns)*	P _{out}	19	Watts (±10%)
Emitter Width	W	95	μm
Spectral Width FWHM	Δλ	15	nm
Slope Efficiency	η	0.35	W/A
Fast Axis Div.	ΘΤ	28	deg FWHM
Slow Axis Div.	Θ	10	deg FWHM
Electrical	Symbol		Units
Power Conversion Eff.	η	5	%
Operating Current (<10ns)	lop	120	А
Operating Current (150ns)	lop	60	А
Threshold Current	Ітн	0.7	А
Operating Voltage	V _{op}	6.2	V
Duty Cycle	DC	0.1	%
Mechanical	Symbol	Range	Units
Operating Temp.**		-40 to 60	°C
Storage Temp.		-40 to 80	°C

*Specified values are rated at a constant heat sink temperature of 20°C.

**High temperature operation will reduce performance and MTTF.

Unless otherwise indicated all values are nominal.

^{*}Available Lenses & Caps


Part Number	Description		
TO56-114	TO56 Uncapped		
TO56-114-116	TO-56 Cap FAC f=590μm, 2.8mm Lg		
TO56-114-126	TO-56 Cap, Lens Matched f=171μm, 2.8mm Lg		
TO56-114-138	TO-56 Cap		



SemiNex Laser Diodes TO56-114

Graphs & Data

Typical TO56 L-I-V Characteristics










Mechanical Drawing TO56-114





All statements, technical information and recommendations related to the product herein are based upon information believed to be reliable or accurate. The accuracy or completeness herein is not guaranteed, and no responsibility is assumed for any inaccuracies. The user assumes all risks and liability whatsoever in connection with the use of a product or its application. SemiNex Corporation reserves the right to change at any time without notice the design, specification, deduction, fit or form of its described herein, including withdrawal at any time of a product offered for sale herein. Users are encouraged to visit www.seminex.com for the latest data. SemiNex Corporation makes no representations that the products herein are free from any intellectual property claims of others. Please contact SemiNex for more information. 2024 SemiNex Corporation






Mechanical Drawing

TO56-114-138

TO56-114-126

TO56-114-116





All statements, technical information and recommendations related to the product herein are based upon information believed to be reliable or accurate. The accuracy or completeness herein is not guaranteed, and no responsibility is assumed for any inaccuracies. The user assumes all risks and liability whatsoever in connection with the use of a product or its application. SemiNex Corporation reserves the right to change at any time without notice the design, specification, deduction, fit or form of its described herein, including withdrawal at any time of a product offered for sale herein. Users are encouraged to visit www.seminex.com for the latest data. SemiNex Corporation makes no representations that the products herein are free from any intellectual property claims of others. Please contact SemiNex for more information. 2024 SemiNex Corporation



SemiNex Corporation • 153 Andover Street, Suite 201, Danvers, MA 01923 • 978-326-7700 • sales@seminex.com