

# 62138 HLX 100W 12V 40/CS 1/SKU



### Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

### Areas of application

- Microscopy
- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Surgical & Dental Overhead

## Product datasheet

### Technical data

### **General Product Information**

Product number (Americas)	54256	
Product name (Americas)	62138 HLX 100W 12V 40/CS 1/SKU	
Family brand	XENOPHOT (HLX)	
ANSI code	-	
Global order reference	62138 HLX	


### **Electrical Data**

Nominal wattage	100 W
Nominal voltage	12.0 V
Type of current	AC

### **Photometric Data**

Nominal luminous flux	3050 lm	
Illuminated field	2.4*1.8 mm²	
Color temperature	3350 K	
Color rendering index Ra	100	
Light center length (LCL)	27.0 mm	
Light center length (LCL) - (in)	1.063 in	

## **Physical Attributes & Dimensions**



Lamp base	G6.35
Diameter (in)	0.472 in
Diameter	11.5 mm
Length	37.0 mm
Product weight	5.10 g

### Product datasheet

### **Operating Conditions**

Burning position	p90/p15

#### Lifetime Data

Nominal lifetime	50 hr

### **Environmental & Regulatory Information**

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Primary article identifier 4050300242958		
Declaration no. in SCIP database	No declarable substances contained	
Candidate list substance 1	No declarable substances contained	

### Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

### **Packaging Information**

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54256	4050300242958	FOLDING BOX	1		
54256	4050300890845	SHIPPING BOX	40	5.9 in x 4.4 in x 4.6 in	0.9 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.