


Features

- High optical power
- High reliability
- Spectral Selectivity
- Easy to use in lock-in circuits
- Parabolic reflector with window




Applications

- Measuring equipment
- Gas analysis (CO₂, HI)
- Analytical spectral devices

Options

- Power supply: [LED Driver D-31M](#)



LED chip

Description

Light emitting diode **LED15HP-PRW** demonstrates typical maximum of emitting wavelength of $\lambda_p = 1.53 \mu\text{m}$ ($I = 100 \text{ mA}$, $f = 0.5 \text{ KHz}$, duty cycle: 50%).

Light emitting diode **LED15HP-PRW** is equipped with quartz window. The components is mounted in a standard 5.5 mm TO-18 package with parabolic reflector (PR).

Related products: **LED15HP-PRW** can be used in optical pair with our [PD24](#) photodiodes.

General characteristics

Package	Parameter	Symbol	Value	Unit
TO-18 with PRW	Maximum operating current	I_{QCW}^*	150	mA
		I_{Pulsed}^{**}	1500	
	Soldering temperature	T_s	+ 230	°C
	Operating temperature	T_{opr}	- 30...+ 50	°C
	Storage temperature	T_{stg}	- 55...+ 60	°C
	Weight	m	0.68	g
	Size	D	9.0	mm
		H	18.5	

* Quasi-CW mode: Repetition rate: 0.5 kHz, pulse duration: 1 ms, duty cycle: 50%

** Pulse mode: Repetition rate: 0.5 kHz, pulse duration: 2 μs , duty cycle: 0.1%


Electrical and optical characteristics

Parameter	Symbol	Condition	Min	Max	Unit
Peak emission wavelength	λ_p	$I_F = 100 \text{ mA}$	$\lambda_{typ} = 1.53$		μm
			1.51	1.55	
Spectral FWHM	$\Delta\lambda$	$I_F = 100 \text{ mA}$	90	150	nm
Pulse optical power	P^*_{QCW}	$I_F = 100 \text{ mA}$	2.5	5.0	mW
	P^{**}_{Pulsed}	$I_F = 1000 \text{ mA}$	10	20	
Forward voltage	V_F	(*)	0.5	0.8	V
Switching time	τ		10	30	ns


* Quasi-CW mode: repetition rate: 0.5 kHz, pulse duration: 1 ms, duty cycle: 50%, current: 100 mA

** Pulse mode: repetition rate: 0.5 kHz, pulse duration: 2 μs , duty cycle: 0.1%, current: 1 A


Electroluminescence spectra




Pulse optical power vs. current




Current vs. voltage



Field pattern



▼ TO-18 package with PR - dimensions (mm)



Pin	Description
① Common to case	Diode (cathode)*
②	Diode (anode)*

* **Attention:** Pin polarity can be changed.