


1539nm DFB Tunable Laser diode (TO39 Package)



Description:

The PL-DFB-1539-A-A81 1539nm DFB laser diode module made by LD-PD is a cost effective, highly coherent laser source. The DFB laser diode chip is packaged in an industry standard hermetically sealed TO39 package with TEC and PD Built in.

Features:

- Narrow Linewidth < 2MHz
- Excellent wavelength control and stability
- Industry Standard 14 pin Butterfly package
- Mode-Hop free tuning
- Excellent reliability
- Customer specific wavelengths available

Application:


- Tunable diode laser absorption spectroscopy
- C₂H₂ Monitoring

Laser Specifications:


Tsub=25°C, CW bias unless stated otherwise

Parameter	Symbol	Min	Typ	Max	Unit
Centre Wavelength	λ	1538.5	1539.0	1539.5	nm
Side Mode Suppression Ratio	SMSR	30	40		dB
Threshold Current	I _{th}		20	30	mA
Operating Current	I _{op}		80	120	mA
Chip output Power	P _f	10	15	30	mW
Quantum Efficiency	η	0.08	0.12		mW/mA
Current Tuning Coefficient	$\Delta\lambda/\Delta I$		0.015		nm/mA
Temperature Tuning Coefficient	$\Delta\lambda/\Delta T$		0.12		nm/K
Forward Voltage	V _f		1.3	2	V
Thermistor Resistance	R _T	9.5	10	10.5	K Ω
Thermistor Temp. Coefficient			-4.4		%/°C


Spectrum:




L-I Curve:




DFB Linewidth Testing Result:



Beam Quality:



2D



3D

The image displays a grayscale histogram of a noisy image on the left and the corresponding FlyCapture2 Histogram window on the right. The histogram shows a distribution of pixel intensities from 0 to 1280, with a peak around 640. The FlyCapture2 Histogram window includes a plot of the histogram and a table of statistics.

Histogram Row / Column Plot		
Plot Mode	Display	Function
☒ Column	☒ Grey	☐ Maximum
☐ Row	☐ Red	☒ Mean
	☐ Green	☒ Minimum
	☐ Blue	

Item	Unit	Min	Typ	Max
Case Temperature	°C	-5	25	70
Chip Temperature	°C	+10	25	40
Operating Current	mA	0	100	120
Forward Voltage	V	0.8	1.2	1.8
TEC Current	A	-	-	1.2
Reverse Voltage (LD)	V	-	-	2.0
Reverse Voltage (PD)	V	-	-	20

Ordering Info:

PL-DFB-□□□□-☆-A8▽-TO39

□□□□: Wavelength

1539: 1539nm

1653.7: 1653.7nm

☆: Output Power

A: 10mW

B: 20mW

▽: Wavelength Tolerance

1: $\pm 1\text{nm}$ 2: $\pm 2\text{nm}$