

HL6756MG



Description

This 670 nm, 15 mW TO packaged laser diode is a compact light source that outputs a single transverse mode and is suited for a variety of applications such as test and measurement or sensing. It is packaged in a standard Ø5.6 mm TO can package and has an A pin configuration. This laser diode is compatible with our line of laser diode and TEC controllers as well as our selection of collimation solutions and TO can laser diode mounts.

Specifications

Absolute Maximum Ratings ^a	
Specification	Maximum
Optical Output Power, CW	15 mW
LD Reverse Voltage	2 V
PD Reverse Voltage	20 V
Operating Temperature	-10 °C to 60 °C
Storage Temperature	-40 °C to 85 °C



a. Absolute Maximum Rating specifications should never be exceeded. Operating at or beyond these conditions can permanently damage the laser.

HL6756MG Specifications ^a				
	Symbol	Min	Typical	Max
Center Wavelength @ P _{op} ^b	λ _o	660 nm	670 nm	680 nm
Threshold Current	I _{TH}	-	15 mA	30 mA
Operating Current, CW @ P _{op} ^b	I _{op}	-	35 mA	45 mA
Operating Voltage @ P _{op} ^b	V _{op}	-	2.3 V	2.7 V
Slope Efficiency	η	-	1 mW/mA	-
Beam Divergence (FWHM) @ P _{op} ^b	Parallel	θ _{//}	5°	8°
	Perpendicular	θ _⊥	20°	24°
Monitor Current @ P _{op} ^b	I _{PD}	0.5 mA	1.5 mA	2.5 mA

a. T_{CASE} = 25 °C if not specified.

b. P_{op} = 15 mW

Drawing

