



**LP660-SF50**


### Description

Thorlabs' Single Mode Pigtailed Laser Diodes are standard TO-packaged diodes that have been pigtailed to a 1 m long single mode fiber with an FC/PC connector. Each unit is tested before shipment. Please refer to the unit-specific test datasheet for optimal operating parameters.

### Specifications

Absolute Maximum Ratings <sup>a</sup>	
LD Reverse Voltage (Max)	2 V
PD Reverse Voltage (Max)	30 V
Optical Output Power	55 mW
Operating Temperature	0 to 50 °C
Storage Temperature	-10 to 65 °C
Pin Code	5C

- a. Absolute Maximum Rating specifications should never be exceeded. Operating at or beyond these conditions can permanently damage the laser.



LP660-SF50 Specifications			
	Min	Typ.	Max
Wavelength	650 nm	660 nm	670 nm
Threshold Current <sup>b</sup>	-	60 mA	75 mA
Optical Output Power	40 mW	50 mW	55 mW
Slope Efficiency <sup>b</sup>	0.15 mW/mA	0.5 mW/mA	-
Operating Current @ P <sub>0</sub> = 50 mW <sup>b</sup>	-	140 mA	200 mA
Operating Voltage @ P <sub>0</sub> = 50 mW <sup>b</sup>	-	2.3 V	-
Monitor Current @ P <sub>0</sub> = 50 mW <sup>b</sup>	-	0.5 mA	-
Fiber Specifications			
Fiber	SM600		
Connector	FC/PC		

- b. Temperature = 25 °C

## Drawing

