


## 830 nm Fabry-Perot Laser Diode, 250 mW

L830H1



### Description

The L830H1 830 nm Fabry-Perot single spatial mode laser diode is based on quantum well epitaxial layer growth and a highly reliable ridge waveguide structure. This diode features high optical output power and slope efficiency. The L830H1 Ø9 mm TO-can package discrete laser diode is a compact light source suited for many applications.

### Specifications

Absolute Maximum Ratings <sup>a</sup>	
LD Reverse Voltage (Max)	2 V
Absolute Max Current	400 mA
Absolute Max Power	270 mW
Operating Case Temperature	20 to 50 °C
Storage Temperature	-10 to 65 °C
Pin Code	H

a. Please note that exceeding the absolute maximum ratings above may cause damage to the device.




L830H1 <sup>a</sup>				
	Symbol	Min	Typical	Max
Center Wavelength	$\lambda_c$	825 nm	830 nm	835 nm
Spectral Bandwidth (RMS)	$\Delta\lambda$	-	0.5 nm	2 nm
Output Power CW @ $I_{OP}$	$P_{CW}$	240 mW	250 mW	-
Threshold Current	$I_{TH}$	-	65 mA	80 mA
Operating Current CW	$I_{OP}$	-	-	400 mA
Slope Efficiency	$\Delta P / \Delta I$	-	0.85 W/A	-
Forward Voltage	$V_F$	-	2.0 V	2.5 V
Transverse Beam Divergence Angle (FWHM) <sup>b</sup>	$\theta_T$	-	18°	22°
Lateral Beam Divergence Angle (FWHM) <sup>b</sup>	$\theta_L$	-	8°	10°


a.  $T_{case} = 25^\circ\text{C}$

b. CW at 350 mA


## Typical Performance Plots



The data above was measured at 25 °C.



The data was obtained using the CCS175 Compact Spectrometer and the device held at 25 °C.



## Drawing

