

DATASHEET**Diode Lasers****FACTOR SERIES
FIBER-COUPLED DIODE LASER MODULE**

The FACTOR Series offers the highest efficiencies and best reliability for pump wavelengths in the range of 88x nm, 793 nm and 976 nm for pumping Nd^{3+} , Tm^{3+} and Yb^{3+} doped materials respectively. It is available between 1 and 22 single emitters, ranging from power levels of a few Watts up to 400 W.

**FEATURES**

- Robust package
- Fixed fiber
- VBG locking for wavelength stabilization
- Back reflection filter for 1064 nm laser light

APPLICATIONS

- Solid-state laser pumping

**Coherent, Inc.**

5100 Patrick Henry Drive, Santa Clara, CA 95054
p. (800) 527-3786 | (408) 764-4983
f. (408) 764-4646

tech.sales@coherent.com www.coherent.com

DATASHEET

Parameter	MDL878.6FCSE220HS22.1FACTOR200VBG
Package	Fiber-Coupled Single Emitters
OPTICAL PARAMETERS ¹	
Center Wavelength Range ³ (nm)	878.6
Center Wavelength Tolerance ³ (nm)	±0.6
Output Power ² (W)	220
Operating Condition	CW
Spectral Width (90% power content) (nm)	≤1
Wavelength Locked Output Power Range	100W to 220W
Slope Efficiency (W/A)	≥19
Wavelength Temp. Coefficient (nm/°C)	~0.01
Numerical Aperture (NA)	≥90% in 0.16
FIBER PARAMETERS ⁵	
Fiber Core Diameter (μm)	200 ±5
Fiber Cladding Diameter (μm)	280 ±6
Fiber Coating Diameter (μm)	450±30
Fiber Loose Tubing Diameter (mm)	2.2
Numerical Aperture (NA)	0.22 ±0.02
Fiber Length (m)	≥1.5
Fiber Termination	SMA905
ELECTRICAL PARAMETERS ¹	
Power Conversion Efficiency (%)	≥45
Threshold Current (I _{TH}) (A)	≤2
Operating Current (I _{OP}) (A)	≤13
Operating Voltage (V _{OP}) (V)	≤40
THERMAL PARAMETERS	
Operating Temperature Range ^{2,3,4} (°C)	+20 to +30
Storage Temperature Range ^{3,4} (°C)	0 to +55
Recommended Heatsink Capacity (W)	300
Maximum Soldering Temperature for Electrical Leads (°C)	320
Maximum Soldering Time per Lead (s)	10
MECHANICAL PARAMETERS	
Size (mm ³) [W x D x H]	97 x 76 x 12.5
Weight (kg)	0.65

Notes:

- 

1. Based on 25°C reference temperature.

2. Reduced lifetime if used above nominal operating conditions.

3. Coherent, Inc.

4. 5100 Patrick Henry Drive, Santa Clara, CA 95054

5. Non-detachable fiber.
- 100 Patrick Henry Drive, Santa Clara, CA 95054

p. (800) 527-3786 | (408) 764-4983

f. (408) 764-4646

tech.sales@coherent.com www.coherent.com

DATASHEET


**Coherent, Inc.**

5100 Patrick Henry Drive, Santa Clara, CA 95054

p. (800) 527-3786 | (408) 764-4983

f. (408) 764-4646

tech.sales@coherent.com www.coherent.com

DATASHEET**Coherent, Inc.**

5100 Patrick Henry Drive, Santa Clara, CA 95054

p. (800) 527-3786 | (408) 764-4983

f. (408) 764-4646

tech.sales@coherent.com **www.coherent.com**