

Pigtailed Laser Diode, SMF

LP705-SF15

Description

Thorlabs' Single Mode Pigtailed Laser Diodes are standard TO-packaged diodes that have been pigtailed to a 1 m long single mode fiber with an FC/PC connector. Each unit is tested before shipment; please refer to the unit-specific test datasheet for optimal operating parameters.




Specifications

Specification	Value
LD Reverse Voltage (Max)	2 V
PD Reverse Voltage (Max)	20 V
Optical Output Power	15 mW (Typ.) 20 mW (Max)
Operating Temperature	0 to 50 °C
Storage Temperature	-10 to 65 °C
Pin Code	5C
Fiber	SM600
Connector	FC/PC

Specification	Min	Typ.	Max
Wavelength	695 nm	705 nm	715 nm
Threshold Current*	-	30 mA	60 mA
Slope Efficiency*	0.3 W/A	0.5 W/A	-
Operating Current @ $P_O = 15$ mW*	-	55 mA	80 mA
Operating Voltage @ $P_O = 15$ mW*	-	2.3 V	2.7 V
Monitor Current @ $P_O = 15$ mW*	0.15 mA	0.30 mA	0.60 mA

*Temperature = 25 °C

Drawings



USA, Canada, and South America

Thorlabs, Inc.
435 Route 206
Newton, NJ 07860, USA

Tel: 973-579-7227
Fax: 973-300-3600

Europe

Thorlabs GmbH
85221 Dachau, Germany
Tel: +49-(0)8131-5956-0

Scandinavia

Thorlabs Sweden AB
431 35 Mölndal, Sweden
Tel: +46-31-733-30-00

UK and Ireland

Thorlabs LTD.
Cambridgeshire CB7 4EX, GB
Tel: +44 (0)1353-654440

Japan and Asia

Thorlabs Japan Inc.
Nerima-ku, Tokyo 179-0081, Japan
Tel: +81-3-6915-7701

France

Thorlabs SAS
78600 Maisons-Laffitte, France
Tel: +33 (0) 970 444 844

China

Thorlabs China
Shanghai, China
Tel: +86 (0)21-60561122

