

675nm, 400μm, Conduction-Cooled, Single Bar, Fiber-Coupled Module

Features

- High coupling efficiency
- High brightness
- Sealed housing
- Standard fiber coupling (HP-SMA) for 400μm NA 0.22



Device Specification

Optical Parameters ¹	Units	
Center Wavelength Range ³	nm	675
Center Wavelength Tolerance	nm	±3
Output Power ²	W	10
Spectral Width (FWHM)	nm	<2.0
Slope Efficiency	W/A	>0.7
Wavelength Temp. Coefficient	nm/°C	~0.16

Fiber Parameters		
Numerical Aperture	NA	0.22
Fiber Core Diameter	μm	400
Fiber Connector	HP-SMA 905 with Free Standing Fiber Tips	

Electrical Parameters ¹		
Power Conversion Efficiency	%	>15
Threshold Current (I_{TH})	A	<12
Operating Current (I_{OP})	A	<30
Operating Voltage (V_{OP})	V	<2.2

Thermal Parameters		
Operating Temperature ^{3, 4}	°C	+20 to +30
Storage Temperature ⁴	°C	0 to +55
Recommended Heatsink Capacity	W	70

Optional

True unpolarized output is available as an option.

¹Data at 20°C cold plate temperature.

²Reduced lifetime if used above nominal operating conditions.

³Others available upon request.

⁴A non-condensing environment is required for storage and operation below the ambient dew point.

DILAS
The diode laser company.

DI-062012