Your Source For InfraRed
HAWKEYE TECHNOLOGIES

IR-12K EMITTER

DATASHEET

Infrared emitter designed for NDIR gas analysis and optical sensing, offering stable performance and long operational life.




General Information

Key Features: Stable characteristics (bare minimum resistance drift over life)

Emitter Type	Coil Type, Supported
Operation Mode	Steady
ROHS	Compliant
Reflector Option	Parabolic, Elliptical
Active Area	3.5 × 3.5 mm
Recommended Voltage	6V
Operation Life At 11 W Power*	≥ 50,000 H
Package Type	Customized, No Cap Available

*Max/Recommended. Higher input will impact emitter's life.



*All dimensions in mm

Application Notes

This emitter is designed to operate at elevated temperatures, with the radiating element reaching up to approximately 1000 °C. Such high operating temperatures must be carefully considered in system design and thermal management.

During operation, the package temperature may rise to approximately 100 °C or higher, depending on operating conditions.

The emitter produces infrared radiation primarily within the wavelength range of 2 to 10 µm, with a peak emission near 2.5 µm.

A parabolic reflector is recommended to increase the radiation flux reaching the detector. At a 6.75” emitter–detector distance, the reflector increases the radiation intensity by approximately 14×.

This device is suitable for use in a wide range of infrared spectroscopic applications, including as a radiation source in IR spectrometers.


+1 (401)-320-8673
info@hawkeyetechnologies.com
hawkeyetechnologies.com

Specifications subject to change without notice.
Please visit our website for the most up to date information.

Emitter Ratings

Parameter	Symbol	Value, Typical	Unit	Notes
Cold Resistance	Rc	3.2	Ohm	At room temp
Input Power	P	11	W	-
Input Voltage	V	6	V	-
Input Current	I	1.8	A	-
Operating Resistance	Rop	3.3	Ohm	-
Active Area Temp	T	1000	°C	Environment at 25°C


IR-12K. Power (W) and Temperature (°C) vs Voltage (V)




+1(401)-320-8673
info@hawkeyetechnologies.com
hawkeyetechnologies.com

Specifications subject to change without notice.
Please visit our website for the most up to date information.

IR-12K. Emission (a.u.) vs Wavenumber (cm^-1)




IR-12K. Emission (a.u.) vs Wavelength (um).



+1(401)-320-8673
info@hawkeyetechnologies.com
hawkeyetechnologies.com

Specifications subject to change without notice.
Please visit our website for the most up to date information.

IR-12K. Radiance Distribution over Wavelengths.



+1(401)-320-8673
info@hawkeyetechnologies.com
hawkeyetechnologies.com

Specifications subject to change without notice.
Please visit our website for the most up to date information.